

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 19 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS													
	<p style="text-align: center;">Reestablishment of the Survey Executed by Woods and Myrick in 1881 and the Resurvey Executed by R.E. Williams in 1991</p> <hr/> <p>Beginning at the cor. of secs. 13, 18, 19, and 24, monumented with a stainless steel post, 2$\frac{1}{2}$ ins. diam., set in a collar of stone, with brass cap mkd. as described in the field notes of the 1991 resurvey.</p> <p>From this corner U.S. Coast and Geodetic Survey station "SNIPE", monumented with a standard brass tablet, stamped SNIPE 1957, set in a concrete post, bears S. 43°00'50" W., 151.780 chs. dist.</p> <p>N. 0°33'20" E., bet. secs. 13 and 18.</p> <p>Along east edge of a graded road which bears N-S.</p>												
41.026	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, monumented with a stainless steel post, 2$\frac{1}{2}$ ins. diam., projecting 4 ins. above the ground with brass cap mkd. as described in the field notes of the 1991 resurvey.</p> <hr/> <p>N. 0°01'50" W., beginning new measurement.</p>												
10.230	Point for the S-N $\frac{1}{64}$ sec. cor. of secs. 13 and 18; not monumented.												
20.460	Point for the N $\frac{1}{16}$ sec. cor. of secs. 13 and 18. Point falls on east edge of a graded road, where it is impracticable to establish a permanent monument.												
40.20	Power transmission line, E-W.												
40.920	The cor. of secs. 7, 12, 13, and 18, monumented with a stainless steel post, 2 $\frac{1}{2}$ ins. diam., set in a collar of stone, with brass cap mkd. as described in the field notes of the 1991 resurvey.												
	<p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 19 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by Woods and Myrick in 1882</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 ins. diam., set flush with the surface of the ground at the corner of fences projecting north and east, with brass cap mkd.:</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">CLARK COUNTY</td> </tr> <tr> <td colspan="2">T19S R62E</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td colspan="2">NEVADA</td> </tr> </table> </div> <p>This monument was set by the U.S. Army Corps of Engineers as shown on Record of Survey, File 1, Page 10, on file in the office of the Clark County Recorder; it is accepted as the best available evidence of the position of the original corner.</p>	CLARK COUNTY		T19S R62E		S18	S17	<hr/>		S19	S20	NEVADA	
CLARK COUNTY													
T19S R62E													
S18	S17												
<hr/>													
S19	S20												
NEVADA													