

022

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors J.C. Smyles and A.J. Hatch in 1872, and a Portion of the Dependent Survey Executed by U.S. Deputy Surveyor J.B. Menardi in 1905</p> <hr/> <p>From the cor. of secs. 11 and 12, perpetuated by Don M. McHarg, Nevada Professional Land Surveyor No. 4787, monumented with a concrete cylinder, 2$\frac{1}{2}$ ins. diam., firmly set, flush in pavement, on north shoulder of Vista Boulevard, with an aluminum disk, 2 ins. diam., marks are unreadable. This aluminum disk is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>CORNER NOT REMONUMENTED</p> <p>This corner is located 0.26 chs. N. of Vista Boulevard, bearing E. and W. From this same corner, a corner of fences, extending N. and W., bears N. 1° E., 0.54 chs. dist.</p> <p>S. 89°01'40" W., on the S. bdy. of sec. 11.</p> <p>Over nearly level land, covered with native grass.</p> <p>4.375 The closing cor. of secs. 13 and 14, hereinafter described.</p> <p>40.049 The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, remonumented by E.A. Taylor, Nevada Registered Engineer No. 468, monumented with an iron pipe, 2 ins. diam., 18 ins. long, firmly set, projecting 4 ins. above the ground, with the original corner stone, a basalt stone, 10X7X6 ins., plainly mkd. $\frac{1}{4}$ on a face, buried alongside the iron pipe as recorded in Washoe County, Nevada, Record of Survey No. 95.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R20E</p> <p>S11</p> <p>$\frac{1}{4}$ ———</p> <p>S14</p> <p>2000</p> </div> <p>Deposit the original cornerstone alongside the stainless steel post and insert the iron pipe inside the stainless steel post.</p> <p>This corner is located at corner of fences, extending S., E. and W.</p> <hr/> <p>Reestablishment of the Completion Survey Executed by U.S. Deputy Surveyor J.B. Menardi in 1905</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with a stainless steel post, 2$\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of T. 20 N., R. 20 E., executed under Group No. 786.</p>
--------	---