

038

SUBDIVISION OF SECTION 6,
T. 13 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
77.744	<p>A stainless steel post, 28 ins. long, 2¹/₂ ins. diam., set 19 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 71¹/₂° E., 11.7 lks. dist., with brass cap mkd. RM CW 1/16 S6 1995 and an arrow pointing to the cor.</p> <p>Cor. is located on timbered SW. slope.</p> <p>The ¹/₄ sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, and in a mound of stone, 2 ft. diam., to top, with brass cap mkd. as described in the dependent resurvey of T. 13 N., R. 19 E., executed under Group No. 620, from which the original bearing tree</p> <p style="padding-left: 40px;">A jeffrey pine, 36 ins. diam., bears WEST, 20 lks. dist., with scribe marks 4S and BT visible on 2 chopped open blazes.</p> <p>and the 1939 bearing trees</p> <p style="padding-left: 40px;">A jeffrey pine, 26 ins. diam., bears N. 9° E., 81 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A white fir, 32 ins. diam., bears N. 25° W., 54 lks. dist., with healed blaze.</p>
20.008	<p>From the C-E ¹/₁₆ sec. cor. of sec. 6.</p> <p>N. 0°21'00" E., on the N. and S. center line of the NE¹/₄ of sec. 6.</p> <p>Point for the NE ¹/₁₆ sec. cor. of sec. 6, at intersection with the E. and W. center line of the NE¹/₄.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 22 ins. in the ground, over a plastic-encased magnet at base, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S6 1996</p> <p>from which</p> <p style="padding-left: 40px;">A western white pine, 23 ins. diam., bears S. 43° W., 81¹/₂ lks. dist., mkd. NE ¹/₁₆ S6 BT.</p> <p style="padding-left: 40px;">A western white pine, 31 ins. diam., bears N. 17° W., 81 lks. dist., mkd. NE ¹/₁₆ S6 BT.</p> <p>Cor. is located on SSE. slope with large granite boulders.</p>
25.010	<p>Point for the C-S-N-NE ¹/₂₅₆ sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 23 ins. in the ground, over a plastic-encased magnet at base, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>