SUBDIVISION OF SECTION 1, T. $23^{1}/_{2}$ N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 23 ¹ / ₂ N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	
	From the $^{1}/_{4}$ sec. cor. of secs. 1 and 1, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set in a collar of stone, with brass cap mkd. as described in the field notes of T. 23 N., R. 49 E., executed under Group No. 113, from which the original bearing trees
	A juniper, 16 ins. diam., bears N. 71° E., 100 lks. dist., with illegible scribing visible on partially healed blaze. (Record tree, cedar)
	A juniper, 20 ins. diam., bears S. 63° W., 103 lks. dist., with the marks " $^{1}/_{4}$ S1 BT" visible on partially healed blaze. (Record tree, cedar)
	Add the marks "T23 $^1/_2$ N R49E T23N 1998" to the brass cap.
	From this corner, Tonkin Spring, bears approximately N. 66° W., about 27 chs. dist.
	N. 0°02'40" E., on the N-S center line of sec. 1.
	Over rolling land, covered with medium sagebrush, scattered juniper, pinon pine, sagebrush, rabbitbrush, cacti and native grasses.
11.90	Trail road, bears irregularly NNW. and SSE.
40.074	Point for the center $^{1}/_{4}$ sec. cor. of sec. 1, at intersection with the E-W center line of sec. 1.
	Set an aluminum post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with aluminum cap mkd.
	T23 1/2N R49E C 1/4 S 1
	1998
43.00	Trail road, bears irregularly NNE. and SSW.
44.70	Single wood pole power line, bears N. $62^{1}/_{2}^{\circ}$ E. and S. $62^{1}/_{2}^{\circ}$ W.
45.60	Improved gravel road, bears irregularly ENE. and WSW.
54.30	Fence, bears irregularly E. and W.
55.092	Point selected for the witness cor. to the C-N $^{1}/_{16}$ sec. cor. of sec. 1.
	Set an aluminum post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 28 ins. in and flush with the ground, over a plastic-encased magnet, with aluminum cap mkd.