DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 11 S., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA	
CHAINS	Reestablishment of the Independent Resurvey Executed by C.S. Swanholm, U.S. Cadastral Engineer, and R.C. Yundt, U.S. Surveyor, in 1934 Superseding the Survey Executed by W.H. Myrick, U.S. Deputy Surveyor, in 1881
	Beginning at the cor. of secs. 1, 6, 31 and 36, Tps. 11 and 12 S., Rs. 69 and 70 E., monumented with an iron post, 3 ins. diam., set in a mound of stone, with brass cap mkd. as described in the field notes of the 1934 resurvey.
	N. 0°02'30" E., bet. secs. 31 and 36.
35.30	Underground gas pipeline, NE-SW.
40.000	The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., set in a mound of stone, with brass cap mkd. as described in the field notes of the 1934 resurvey.
	N. 0°02′00" E., beginning new measurement.
8.10	Power transmission line, NE-SW.
12.50	Power transmission line, NE-SW.
15.50	Power transmission line, NE-SW.
39.950	The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., set in a mound of stone, with brass cap mkd. as described in the field notes of the 1934 resurvey.
	INDEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 11 S., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA
	This Independent Resurvey Supersedes the Survey Executed by W.H. Myrick, U.S. Deputy Surveyor, in 1881. A diligent search was made for the original corners and none were found.
	From the cor. of secs. 1, 6, 31 and 36, Tps. 11 and 12 S., Rs. 69 and 70 E., hereinbefore described.
	N. 89°58'30" W., bet. secs. 1 and 36.
33.50	Underground gas pipeline, NE-SW.
40.000	Point for the 1/4 sec. cor. of secs. 1 and 36.
	Set a stainless steel post, 28 ins. long, $2^{1}/_{2}$ ins. diam., 16 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.