

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 71 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a portion of the Independent Resurvey Executed by R.C. Yundt, U.S. Surveyor, in 1934 Superseding the Survey Executed by W.H. Myrick, U.S. Deputy Surveyor, in 1881</p> <hr/>
	<p>From the standard sec. cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, encircled in a collar of stone, with brass cap mkd. as described in the field notes of the independent resurvey of the Third Standard Parallel South, through Range 71 East, executed under Group No. 178.</p> <p>Set a carsonite post alongside stainless steel post.</p> <p>S. 89°56'30" E., on the S. bdy. of sec. 32.</p> <p>Over rolling terrain.</p>
9.05	Asphalt road, 36 lks. wide, bears S. 21° E. and N. 21° W.
9.086	<p>Point selected for a standard witness point, at the intersection with the centerline of right-of-way N-57508.</p> <p>Set a PK nail flush with the asphalt surface with 2 in. diam. shiner mkd.</p>
	<p style="text-align: center;">WP S 32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2001</p>
32.043	<p>From this point, Angle Point No. 1 on the centerline of right-of-way N-57508 bears N. 21°09'40" W., 34.297 chs. dist., hereinafter described.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of sec. 5 only, T. 13 S., R. 71 E., determined at the intersection of the S. bdy. of the Tp. with the N-S center line of sec. 5.</p>
	<p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam, 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S5 T13S R71E</p> <p style="text-align: center;">2001</p>
	<p>From this point, the original $\frac{1}{4}$ sec. cor. of sec. 5 bears N. 0°01'00" E., 0.022 chs. dist., monumented with an iron post, 1 in. diam., 36 ins. long, firmly set 24 ins. in the ground with brass cap mkd. as described in the field notes of the independent resurvey of the subdivisions of T. 13 S., R. 71 E., executed under Group No. 178.</p> <p>Add the mks. AM 2001 and bury the original iron post in place, 6 ins. below the surface of the ground.</p>