


METES-AND-BOUNDS SURVEY OF A PORTION OF
 THE CENTERLINE OF RIGHT-OF-WAY N-57508,
 T. 12 S., R. 71 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Cor. is located 5.8 lks. E. of an asphalt road, 36 lks. wide, bears N. 54° E. and S. 54° W.</p>
	<p>Thence N. 53°53'00" E., continuing on the centerline of right-of-way N-57508.</p>
4.470	<p>Intersect the line bet. secs. 29 and 30, at a point from which the cor. of secs. 19, 20, 29 and 30 hereinbefore described bears N. 0°00'40" E., 2.220 chs. dist.</p>
8.231	<p>The witness point of secs. 20 and 29, hereinbefore described.</p> <p>From this point, a control point established by Bulloch Brothers Engineering, Inc. designated as PP22, bears S. 43°08'30" W., 4.675 chs. dist., monumented with a rebar, ⁵/₈ in. diam., projecting 1 in. above ground, with a steel fence post alongside.</p> <p>From this same point, the end tangent of the centerline of right-of-way N-57508 bears N. 53°53'00" E., 36.522 chs. dist. Not monumented.</p>
<hr/> <p>METES-AND-BOUNDS SURVEY IN SECTION 33, T. 12 S., R. 71 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the witness point of secs. 33 and 34, hereinbefore described.</p> <p>Thence S. 64°02'30" W.</p>
12.295	<p>The standard witness point of sec. 33, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>Thence N. 72°25'20" W.</p>
8.391	<p>Point for Angle Point No. 1, sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
<p>T12S R71E</p>  <p>S33</p> <p>AP1</p> <p>2001</p>	
	<p>Thence S. 85°43'40" W.</p>
7.643	<p>Point for Angle Point No. 2, sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>