

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
 (FIRST STANDARD PARALLEL SOUTH),
 T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2¹/₂ ins. diam., 12 ins. in the ground to bedrock, over a magnetic marker, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 35 E ¹/₁₆</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1993</p>
20.258	From this point the original closing cor. of secs. 1 and 2, T. 5 S., R. 66 E., bears SOUTH, 0.040 chs. dist., monumented with an iron post, 2 ins. diam., firmly set projecting 18 ins. above a mound of stone, with brass cap mkd. as described in the field notes of T. 5 S., R. 66 E., executed under Group No. 34.
38.00	Begin sharp descent over W. facing rock bluffs through juniper.
39.868	The standard ¹ / ₄ sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 5 S., R. 66 E., executed under Group No. 34. Add the marks 1993 to the brass cap.
	<hr style="width: 50%; margin: auto;"/> <p>S. 89°37'40" W., beginning new measurement.</p>
29.50	Wash, drains NNW.
39.572	The standard cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set projecting 18 ins. above a mound of stone, with brass cap mkd. as described in the field notes of T. 5 S., R. 66 E., executed under Group No. 34. Add the marks 1993 to the brass cap.
	The cor. is located at the base of a shear rock face, 30 ft. high.
	<hr style="width: 50%; margin: auto;"/> <p>DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 4 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr style="width: 50%; margin: auto;"/> <p>Reestablishment of the Surveys Executed by U.S. Deputy Surveyor E.B. Monroe in 1872 and U.S. Deputy Surveyor R.H. Woods in 1881</p> <hr style="width: 50%; margin: auto;"/>
	From the true point for the standard cor. of Tps. 4 S., Rs. 66 and 67 E., hereinbefore described.
	N. 0°22'30" E., bet. secs. 31 and 36.
	Over rugged, rocky bluffs through pinion pine and juniper.
4.00	Sawmill Canyon, drains NNW.
5.00	Begin sharp ascent over SW. facing rock bluffs.
33.00	Top of ascent; begin descent over N. facing rock bluffs.
40.164	Point for the ¹ / ₄ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.