

248

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 4 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by  
R.H. Woods in 1881

From the cor. of secs. 8, 9, 16 and 17, monumented with an aluminum rod,  $\frac{3}{4}$  in. diam., set in a mound of stone, with an aluminum cap, 3 ins. diam., mkd.

CALIENTE SURVEY MONUMENT

1992 SURVEY

JAMES J OWENS

T4S R67E

|     |     |
|-----|-----|
| S 8 | S 9 |
|-----|-----|

|      |      |
|------|------|
| S 17 | S 16 |
|------|------|

1992

PLS 2884

No map record of this monument was found; it is accepted as a careful and faithful remonumentation of the corner position remonumented by Richard E. Fonger, Professional Land Surveyor No. 4235, in 1989, and shown on an unrecorded Record of Survey map dated July 6, 1990, and as the best available evidence of the position of the original corner; the Fonger monument, an aluminum post and cap, was found lying on the ground a short distance downslope.

At the corner point

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, over a magnetic marker, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T4S R67E

|     |     |
|-----|-----|
| S 8 | S 9 |
|-----|-----|

|      |      |
|------|------|
| S 17 | S 16 |
|------|------|

1994

Deposit the aluminum rod inside and the aluminum post alongside the stainless steel post.

N.  $0^{\circ}25'00''$  W., bet. secs. 8 and 9.

6.50 Draw, drains NW.

18.00 Ridge, bears NW-SE.

19.903 Point for the S  $\frac{1}{16}$  sec. cor. of secs. 8 and 9.

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, over a magnetic marker, and in a collar of stone, with brass cap mkd.

S  $\frac{1}{16}$

|     |     |
|-----|-----|
| S 8 | S 9 |
|-----|-----|

1994