

CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this same corner, National Geodetic Survey control (formerly U.S.C. &amp; G.S. triangulation) station "TRUCKEE" bears S. 37°14'00" E., 102.536 chs. dist., monumented with a standard brass cap, 3 1/2 ins. diam., firmly cemented into a drill hole in a rock outcrop, with top mkd. TRUCKEE 1946 and a triangle.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by J. S. Lawson, U. S. Deputy Surveyor, in 1861, and the Dependent Resurvey Executed by Cadastral Engineer J. W. Hardison and Cadastral Surveyor H. T. Brown, in 1956.</p> <hr/> <p>S. 87°23'50" W., beginning new measurement.</p> <p>Over nearly level land.</p>
1.90	Power line, bears northerly and southerly.
4.20	Improved gravel road, bears NW. and SE.
5.20	Fence, bears NW. and SE.
5.80	Flick ditch, 30 lks. wide, 4 ft. deep, course NW.
15.60	Steamboat Creek, 10 lks. wide, 2 ft. deep, course N. 20° W.
21.589	Point for the W 1/16 sec. cor. of secs. 3 and 34.
	POINT NOT MONUMENTED
25.10	Ditch, 30 lks. wide, 1 ft. deep, course NNE.
26.30	Fence, at base of hills, bears irregularly N. and S.
39.20	Ridge, bears N. and S.
43.178	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron pipe, 3/4 in. diam., 31 ins. long, firmly set in a mound of stone; there is no remaining evidence of the marked stone recovered in the 1956 dependent resurvey. This iron pipe is locally recognized as the position of the original corner, and has been utilized by private surveyors (Washoe County Records Survey Map No. 2146, File No. 1374274, and Survey Map No. 2492, File No. 1617007).</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>