

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by E. H. Dyer, U. S. Deputy Surveyor, in 1863, and a Portion of the Dependent Resurvey Executed by Cadastral Engineer J. W. Hardison and Cadastral Surveyor H. T. Brown, in 1956.</p> <hr/>
	<p>From the N 1/16 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 19 N., R. 20 E., executed under Group No. 366.</p>
	<p>N. 1°36'50" W., bet. secs. 34 and 35.</p>
	<p>Over steep rolling land, through scattered sagebrush and native grass.</p>
6.70	<p>Base of hill.</p>
9.648	<p>Point for the N-N 1/64 sec. cor. of secs. 34 and 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock over a plastic encased magnet, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">N-N 1/64 S 34 S 35 1994</p>
14.472	<p>The N-N-N 1/256 sec. cor. of secs. 34 and 35, determined by Elmer J. Plummer, Nevada Professional Land Surveyor No. 5095, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with yellow plastic cap mkd. RLS 5095, as recorded in Washoe County, Nevada, Survey Map No. 2157, File No. 1383707. This rebar is accepted as a careful and faithful determination of the position of the corner.</p> <hr/>
	<p>N. 1°36'50" W., beginning new measurement.</p>
4.824	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 19 N., R. 20 E., executed under Group No. 366.</p> <hr/>
	<p>N. 89°38'20" W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through scattered sagebrush and native grass.</p>
17.012	<p>The 1/1024 sec. cor. of secs. 27 and 34, determined by persons unknown, monumented with a metal concrete stake, 3/4 in. diam., 30 ins. long, firmly set projecting 6 ins. above the ground, and over a rebar 5/8 in. diam., 18 ins. long, firmly set 24 ins. below the ground. This is accepted as a careful and faithful determination of the position of the corner.</p>