DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 25 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S 1/16 S28|S27 2001
	Raise a mound of stone west of the corner.
40.880	The 1/4 sec. cor. of secs. 27 and 28, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1992-96 resurvey, and a mound of stone west of the corner.
	SUBDIVISION OF SECTION 26, T. 25 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 26 and 35.
	N. 0°10'20" E., on the N-S center line of sec. 26.
20.124	Point for the center S 1/16 sec. cor. of sec. 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.
	C S 1/16|S26 C 2001
40.248	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T25S R59E C 1/4 S26 2001
	Raise a mound of stone west of the corner.
43.750	Intersect the center of tracks of the Union Pacific Railroad, on curve concave southeast.
48.50	Underground petroleum pipelines, NE-SW.
80.976	The 1/4 sec. cor. of secs. 23 and 26, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1992-96 resurvey, and a mound of stone west of the corner.
	From the 1/4 sec. cor. of secs. 25 and 26, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1992-96 resurvey, and a mound of stone west of the corner.