

074

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by
T.A. Magee in 1883

Beginning at the cor. of Tps. 26 and 27 S., Rs. 59 and 60 E., monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY T26S T27S R59E R60E RLS 6199, set in a mound of stone under a granite stone, 20x12x8 ins., mkd. with 6 notches on the north, south, east and west edges. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T26S
R59E R60E
S36 S31
— —
S 1 S 6
T27S

2001

Deposit the rebar inside and the original corner monument alongside the stainless steel post.

N. 89°40'30" W., bet. secs. 1 and 36.

40.525

The 1/4 sec. cor. of secs. 1 and 36, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 1 36 RLS 6199, set in a mound of stone under a granite stone, 12x10x8 ins., mkd. 1/4 on the north face. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T26S R59E
S36
1/4 —
S 1
T27S

2001

Deposit the rebar inside and the original corner monument alongside the stainless steel post.

Raise a mound of stone north of the corner.