DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA	
CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} T26S \ R59E \\ \hline \frac{S32}{s \ 5} \\ T27S \end{array}$
	2001
26.20	Underground telephone cable, NE-SW.
40.483	The 1/4 sec. cor. of secs. 5 and 32, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 5 32 RLS 6199, set flush with the surface of the ground. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as the best available evidence of the original corner position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T26S R59E S32
	1/4 <u>— </u>
	2001
	Deposit the rebar inside the stainless steel post.
	S. 89°52'10" W., beginning new measurement.
40.580	The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 ins. diam., projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the 1932 resurvey executed by R.F. Wilson under Group No. 205, California, and a mound of stone west of the corner.
	DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by T.A. Magee in 1883
	From the cor. of Tps. 26 and 27 S., Rs. 59 and 60 E., hereinbefore described.
	N. 0°02'30" E., bet. secs. 31 and 36.

##