

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

	1. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T26S R59E S18 S17
	S19 S20
	2001
	Deposit the rebar inside and the original corner monument alongside the stainless steel post.
	Raise a mound of stone west of the corner.
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°36′30" W., bet. secs. 17 and 20.
39.665	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T26S R59E
1	$\begin{array}{c} 1/4 \\ \hline \end{array}$
	S20
	2001
	Raise a mound of stone north of the corner.
79.330	The cor. of secs. 17, 18, 19 and 20.
	SUBDIVISION OF SECTION 33, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 4 and 33, on the south boundary of the Tp. hereinbefore described.
	N. 0°12′50" E., on the N-S center line of sec. 33.
12.00	Power transmission line, NE-SW.
40.203	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.