

140

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the survey executed by A. J. Hatch, U.S. Deputy Surveyor, in 1868</p>										
	<p>From the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., determined by John H. Milton III, Nevada Professional Land Surveyor No. 5271, at the corner of fences extending N. and W. monumented with a rebar, 5/8 in. diam., 22 ins. long, firmly set 20 ins. in the ground, with aluminum cap mkd., JOHN H. MILTON III RLS 5271, as shown on Parcel Map recorded as File No. 143502, Pershing County, Nevada. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T27N</td><td>R31E</td></tr> <tr><td>S31</td><td>S32</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td>T26N</td><td></td></tr> </table> <p>1999</p> </div> <p>Place rebar inside the stainless steel post.</p> <p>S. 89°49'30" W., bet. secs. 6 and 31.</p> <p>Over nearly level terrain, along fence.</p>	T27N	R31E	S31	S32	S 6	S 5	T26N			
T27N	R31E										
S31	S32										
S 6	S 5										
T26N											
1.70	Corner of fences extending E. and S. 2° E.										
20.659	Point for the E 1/16 sec. cor. of secs. 6 and 31. Point not monumented.										
41.318	<p>The 1/4 sec. cor. of secs. 6 and 31, remonumented by John H. Milton III, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set 16 ins. in the ground, with aluminum cap mkd., JOHN H. MILTON III RLS 5271, as shown on Parcel Map recorded as File No. 143502, Pershing County, Nevada, with a wooden post, 6x4 ins., 4 ft. long, firmly set alongside, 24 ins. in the ground, mkd. illegibly. This is accepted as a careful and best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T27N</td><td>R31E</td></tr> <tr><td>S31</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 6</td><td></td></tr> <tr><td>T26N</td><td></td></tr> </table> <p>1999</p> </div>	T27N	R31E	S31		1/4	—	S 6		T26N	
T27N	R31E										
S31											
1/4	—										
S 6											
T26N											