

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by H.G. Parker in 1961</p> <hr/>
13.069	<p>Beginning at the cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 1/2 ins. diam., set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the 1961 survey, and a mound of stone west of the corner.</p> <p>Corner is located at the end of a fence which projects east.</p> <p>N. 0°07'00" W., bet. secs. 2 and 3.</p> <p>Point for a witness point at intersection with the westerly right-of-way line of U.S. Highway 95.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">WP S 3 S 2 2001</p>
17.895	<p>Point of intersection with the centerline of U.S. Highway 95. This intersection point was determined from ties made to Nevada Department of Transportation right-of-way monuments.</p> <p>Set a PK nail and shiner in the surface of the highway.</p>
40.008	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1961 survey.</p> <p>From this corner National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "SARCOBATUS", monumented with a standard brass tablet set in concrete, mkd. SARCOBATUS 1949, bears N. 66°18'20" W., 24.349 chs. dist.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 3, T. 8 S., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
39.999	<p>From the 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 2 1/2 ins. diam., projecting 10 ins. above the ground with brass cap mkd. as described in the field notes of the 1961 survey.</p> <p>N. 0°08'00" W., on the N-S center line of sec. 3.</p> <p>The center 1/4 sec. cor. of sec. 3, monumented with a portion of steel fence post, 24 ins. long, projecting 6 ins. above the ground, to which is wired a brass tag mkd. RLS 451. No map record of this monument was found; it is accepted as a careful and faithful determination of the corner position.</p> <p>At the corner point</p>