CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T8S R44E C 1/4 S 3 2001 Deposit the steel fence post with tag alongside the stainless steel post.
	N. 0°08'00" W., beginning new measurement.
22.683	Point for a witness point at intersection with the westerly right-of-way line of U.S. Highway 95, monumented with a portion of steel fence post, 24 ins. long, projecting 6 ins. above the ground, to which is wired a brass tag mkd. RLS 451. No map record of this monument was found; it is accepted as a careful and faithful determination of the point of intersection. At the point of intersection Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. WP C S | 3 C 2001 Deposit the steel fence post with tag inside the stainless steel post.
27.510	Point of intersection with the centerline of U.S. Highway 95. This intersection point was determined from ties made to Nevada Department of Transportation right-of-way monuments. Set a PK nail and shiner in the surface of the highway.
39.984	The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 2 ins. above the ground with brass cap mkd. as described in the field notes of the 1961 resurvey.
	From the 1/4 sec. cor. of secs. 2 and 3.
	N. 89°53'50" W., on the E-W center line of sec. 3.
17.898	Point of intersection with the centerline of U.S. Highway 95. This intersection point was determined from ties made to Nevada Department of Transportation right-of-way monuments. Set a PK nail and shiner in the surface of the highway.
40.159	The center 1/4 sec. cor.