

190

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 23 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by T.A. Magee in 1883 and the Resurveys Executed by C.S. Swanholm in 1931 and H.G. Parker in 1957-58</p> <hr/> <p>Beginning at the cor. of secs. 2, 3, 34 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., set in a collar of stone with brass cap mkd. as described in the field notes of the 1995-96 resurvey executed by R.A. Zaninovich under Group No. 760.</p> <p>S. 89°45'10" W., bet. secs. 3 and 34.</p>
0.50	Power transmission line, NW-SE.
9.999	<p>The E-E 1/64 sec. cor. of secs. 3 and 34, monumented with an iron post, 2 1/2 ins. diam., set in a collar of stone, with brass cap mkd. as described in the field notes of the 1957-58 resurvey.</p> <hr/> <p>S. 89°50'00" W., beginning new measurement.</p>
1.380	Intersect a brass tablet, set in concrete flush with the surface of the ground mkd. COH 299-203 1975.
4.781	Intersect a rebar, 5/8 in. diam., set flush with the surface of the ground, with aluminum cap mkd. CITY OF HENDERSON PLS 7190, and centerline of railroad bears N. 63°42'20" W. and S. 63°42'20" E.
8.182	Intersect a rebar, 5/8 in. diam., set flush with the surface of the ground, with aluminum cap mkd. CITY OF HENDERSON PLS 7190.
10.013	<p>The E 1/16 sec. cor. of secs. 3 and 34, monumented with a rebar, 5/8 in. diam., set flush with the surface of the ground, with aluminum cap mkd.</p> <p style="text-align: center;">CITY OF HENDERSON E 1/16 PLS 7190</p> <p>This monument is accepted as a careful and faithful perpetuation of the 1957-58 corner position referenced by John R. Rinaldi, PLS 7190, in 1996 as shown on Corner Record, Document No. 960404.00988, on file in the office of the Clark County Recorder.</p> <p>From this corner reference monuments, 5/8 in. rebar with aluminum caps mkd. CITY OF HENDERSON PLS 7190 RM and the distance, bear:</p> <p style="text-align: center;">S. 57°57'10" E., 37.89 ft. S. 32°17'40" E., 23.60 ft. S. 42°47'20" W., 26.87 ft. S. 64°11'20" W., 44.65 ft.</p> <hr/> <p>S. 89°45'10" W., beginning new measurement.</p>
10.012	The W-E 1/64 sec. cor. of secs. 3 and 34, monumented with a rebar, 5/8 in. diam., set flush with the surface of the ground, with aluminum cap mkd.