## 217

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,

T. 21 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA CHAINS Reestablishment of the Survey Executed by J.M. Brunt and W.H. Proctor, U.S. Deputy Surveyors, in 1881 and the Resurvey Executed by W.H. Sylvester, Cartographer (Cadastral), in 1955 Beginning at the cor. of secs. 1, 6, 31 and 36, Tps. 21 and 22 S., Rs. 59 and 60 E., monumented with a rebar, 5/8 in. diam., set flush with the surface of the ground, with aluminum cap mkd. R L HAFEN PLS 4428. No map record of this monument was found; it is accepted as the best available evidence of the original corner. N.  $0^{\circ}55'30''$  E., bet. secs. 31 and 36. 20.790 The S 1/16 sec. cor. of secs. 31 and 36, monumented with a rebar, 5/8 in. diam., set flush with the surface of the ground, with aluminum cap mkd. R L HAFEN PLS 4428. No map record of this monument was found; it is accepted as the best available evidence of the 1955 corner position. N. 0°55'30" E., beginning new measurement. 20.783 The 1/4 sec. cor. of secs. 31 and 36, monumented with a rebar, 5/8 in. diam., set flush with the surface of the ground, with aluminum cap mkd. R MROWICKI PLS 11441. This monument was set by Randy W. Mrowicki in 2001 as shown on Record of Survey File 117, Page 100, on file in the office of the Clark County Recorder and is accepted as a careful and faithful reestablishment of the 1955 corner position. DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 21 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by J.M. Brunt and W.H. Proctor, U.S. Deputy Surveyors, in 1881 and the Resurvey Executed by S.R. Lambeth, Cadastral Surveyor, in 1987 From the true point for the 1/4 sec. cor. of secs. 35 and 36, from which the witness corner, hereinafter described, N.  $89^{\circ}45'00"$  E., 0.500 chs. dist. N.  $2^{\circ}12'40"$  W., bet. secs. 35 and 36. 20.049 Point for the N 1/16 sec. cor. of secs. 35 and 36, not monumented. 40.098 The cor. of secs. 25, 26, 35 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., set in a mound of stone, with brass cap mkd. as described in the field notes of the 1987 resurvey. From the 1/4 sec. cor. of secs. 25 and 36, monumented with a

stainless steel post, 2 1/2 ins. diam., set in a collar of stone, with brass cap mkd. as described in the field notes of the 1987 resurvey.

S. 88°43'20" W., bet. secs. 25 and 36.