

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a Portion of the Survey Executed by
E.B. Monroe, U.S. Deputy Surveyor, in 1868

From the cor. of secs. 5, 6, 7 and 8, determined by person(s) unknown, monumented with an iron pipe, 1 in. diam., firmly set, 6 ins. below the asphalt surface of the intersection of Harrigan Road and Drumm Lane. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as the best available evidence of the position of the original corner.

from which accessories established by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1993, as recorded in Churchill County, Nevada, Document No. 274237, Corner Record:

A rebar, 5/8 in. diam., firmly set in a concrete post, 6 ins. diam., projecting 8 ins. above the ground, bears N. 49°50'50" E., 78.8 lks. dist.

A rebar, 5/8 in. diam., firmly set in a concrete post, 6 ins. diam., projecting 8 ins. above the ground, bears S. 72°23'20" W., 104.6 lks. dist.

The corner is located at the eastern side of Harrigan Road, asphalt surface, 60 lks. wide, bears N. and S., and S., 5 lks. dist., from the centerline of Drumm Lane, asphalt surface, 30 lks. wide, extending E.

From this point, National Geodetic Survey control station "C 446" monumented with a brass tablet, 3 ins. diam., firmly set in concrete, flush with the surface of the ground, with top mkd. U.S. NAVY GEOTHERMAL BENCHMARK NO. C 446 1991 SURVEY, bears N. 35°22'00" E., (mean bearing), 145.623 chs. dist.

N. 0°35'30" E., bet. secs. 5 and 6.

20.091

The S 1/16 sec. cor. of secs. 5 and 6, monumented with a steel nail and metal washer, firmly set at the eastern edge of asphalt surface of Harrigan Road, 60 lks. wide, bears N. and S. This position was determined by Wallace A. Cooper, Nevada Professional Land Surveyor No. 749, in 1955, as recorded in Churchill County, Nevada, Book 1, Page 11, of subdivisions, was subsequently redetermined by person(s) unknown and has been adopted and recorded by various professional land surveyors, as indicated on land survey records recorded in Churchill County, Nevada. This is accepted as a careful and faithful determination of the position of the corner.