

SUBDIVISION OF SECTION 6,
T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°09'30" W., beginning new measurement.
20.369	<p>The center N 1/16 sec. cor. of sec. 6, determined by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1988, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the surface of dirt road, 15 lks. wide, bears N. and S., as recorded in Churchill County, Nevada, Document No. 241572, Book 6, Page 37, of records of survey. This position is accepted as a careful and faithful determination of the position of the corner.</p> <hr/>
	N. 0°09'00" W., beginning new measurement.
19.705	<p>A witness corner to the 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., established by person(s) unknown, adopted by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1983, monumented with a rebar, 1/2 in. diam., firmly set, 1 in. below the asphalt surface of Wildes Road, 40 lks. wide, bears E. and W., as recorded in Churchill County, Nevada, Document No. 194109, Book 4, Page 23, of records of survey.</p> <hr/>
	N. 0°09'00" W., beginning new measurement.
0.727	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., determined at record distance from the witness corner and projected bearing from the center N 1/16 sec. cor. of sec. 6, through the witness corner, as recorded in Churchill County, Nevada, Document No. 241572, Book 6, Page 37, of records of survey. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p> <p>The corner is located in canal, bears E. and W., where it is impractical to establish a permanent monument.</p> <p>From this point, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., bears S. 89°50'40" E., 41.029 chs. dist., hereinbefore described.</p> <p>From this same point, the cor. of Tps. 18 and 19 N., Rs. 28 and 29 E., determined by person(s) unknown, bears N. 89°53'40" W., 39.158 chs. dist., monumented with a railroad spike, firmly set, 2 ins. below the asphalt surface of U.S. Highway No. 95. This position has been adopted and recorded by various professional land surveyors, as indicated on survey records recorded in Churchill County, Nevada, and is accepted as the best available evidence of the position of the original corner.</p>