SUBDIVISION OF SECTION 6,

	T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	
10.464	A property corner, established by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1992, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with plastic cap mkd. PLS 7809, as recorded in Churchill County, Nevada, Document No. 272074, Book 19, Page 13, of parcel maps.
	The corner is located at intersection of fence lines, extending E., W. and S.
14.176	A property corner, established by Barry A. Fitzpatrick, Nevada Professional Land Surveyor No. 7809, in 1992, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, as recorded in Churchill County, Nevada, Document No. 272074, Book 19, Page 13, of parcel maps.
	The corner is located at intersection of fence lines, extending E., W. and S.
16.805	From this point, a property corner, established by Lowell D. Emery, Nevada Professional Land Surveyor No. 1251, in 1991, bears S., 2.3 lks. dist., monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the surface of the ground, as recorded in Churchill County, Nevada, Document No. 262236, Book 8, Page 3, of records of survey.
	The corner is located in a fence line, bears E. and W.
20.142	The SE 1/16 sec. cor. of sec. 6.
	N. 89°48'50" W., beginning new measurement.
20.151	The center S 1/16 sec. cor. of sec. 6.
	A METES-AND-BOUNDS SURVEY IN SECTION 6, T. 18 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA
	From Angle Point No. 1, on the E. and W. center line of the SE1/4 of sec. 6, hereinbefore described.
	N. 0°33′10" E., on line 1-2.
5.530	Point for Angle Point No. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.