DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	from which more permanent local survey monuments
	A copper coated steel rod, with unmarked cap, 1 1/2 ins. diam., bears S. 70°41' E., 848.1 lks. dist., 5 ins. below surface of Sugar Pine cul-de-sac, paved surface, in survey monument casing, 8 ins. diam., as recorded in Washoe County, Subdivision Tract Map No. Map 2771A.
	A copper coated steel rod, with cap, 1 1/2 ins. diam., mkd. PLS 4043, bears N. 48°19' W., 902.3 lks. dist., 4 ins. below surface of White Fir Street, paved surface and at N. end of bridge over Truckee River, in survey monument casing, 8 ins. diam., as recorded in Washoe County, Subdivision Tract Map No. 2771A.
	Cor. is located on level paved parking lot of Patagonia Store, 10 ft. North of concrete curb, bears NE and SW.
	From this corner, the 1/4 sec. cor. of secs. 13 and 18, determined by person(s) unknown, bears N. 0°12'10" W., 39.904 chs. dist., monumented with a concrete cylinder, firmly set, 4 ins. diam., projecting 4 ins. above ground, with iron rod, 5/8 in. sq., set flush in center, mkd. with an X on top, accepted by local surveyors, as recorded in Washoe County, Record of Survey Map Nos. 648, 695A and 2017. This is accepted as the best available evidence of the position of the original corner.
	Not remonumented.
	DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 19 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA AND CALIFORNIA
	Reestablishment of a Portion of the Survey Executed by S.W. Foreman, Deputy Surveyor, in 1865, and a Portion of the Dependent Resurvey Executed by E. Voigt, U.S. Transitman, in 1918
	From the cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the 1918 resurvey, alongside of which is a granite stone, $20 \times 13 \times 8$ ins. (Record, $30 \times 10 \times 8$ ins.), with faint marks and in a mound of stone, 3 ft. base, 12 ins. high, from which the remains of a 1918 bearing tree
	A burned pine snag base, 21 ins. diam., bears S. 18° W., 176 lks. dist., no marks visible. (Record, 1.80 chs.)
	and new bearing trees
	A Jeffrey pine, 13 ins. diam., bears N. 54° E., 82 lks. dist., mkd. T20N R18E S32 BT.
	A Jeffrey pine, 8 ins. diam., bears S. 10° W.,
	110 lks. dist., mkd. X BT.

132