

232

DEPENDENT RESURVEY OF PORTIONS
OF THE SUBDIVISION OF SECTION 6,
T. 21 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 85°35'50" W., beginning new measurement.
19.340	The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., identical with Angle Point No. 4, Lot 22, sec. 6.
<hr/> <p>FURTHER SUBDIVISION OF SECTION 6, T. 21 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
From the E 1/16 sec. cor. of secs. 6 and 7.	
N. 1°59'40" W., on the N-S center line of the SE1/4 of sec. 6.	
4.864	The center S-S-SE 1/256 sec. cor. of sec. 6, monumented with a rebar, 5/8 in. diam., set in a collar of stone, with aluminum cap mkd. SF TURNER RLS 1803. This monument was set by Stephen F. Turner in 1974 as shown on Parcel Map, File 3, Page 72, on file in the office of the Clark County Recorder and is accepted as a careful and faithful determination of the corner position.
<hr/>	
N. 1°59'40" W., beginning new measurement.	
4.859	The center S-SE 1/64 sec. cor. of sec. 6, monumented with a rebar, 5/8 in. diam., set in a collar of stone, with aluminum cap mkd. SF TURNER RLS 1803. This monument was set by Stephen F. Turner in 1974 as shown on Parcel Map, File 3, Page 72, on file in the office of the Clark County Recorder and is accepted as a careful and faithful determination of the corner position.
At the corner point	
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.	
<p>S 6 C-S-SE 1/64 1996</p>	
Deposit the rebar inside the stainless steel post.	
<hr/>	
N. 2°03'40" W., beginning new measurement.	
4.859	Point for the center N-S-SE 1/256 sec. cor. of sec. 6. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in concrete, in the cut bank at the east edge of a road which bears N-S, with top mkd.
<p>S 6 C-N-S-SE 1/256 1996</p>	