

FURTHER SUBDIVISION OF SECTION 6,  
T. 21 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the center N-S-SE 1/256 sec. cor. of sec. 6.
	N. 87°44'00" W., on the E-W center line of the NE1/4 SW1/4 SE1/4 of sec. 6.
10.357	The center N-SW-SE 1/256 sec. cor. of sec. 6.
	N. 87°32'30" W., on the E-W center line of the NW1/4 SW1/4 SE1/4 of sec. 6.
10.361	The center N-S-S 1/256 sec. cor. of sec. 6.
	CORRECTIVE RESURVEY OF PORTIONS OF THE SUBDIVISION OF SECTION 6, T. 21 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA
	Correction of the Survey Executed by B.R. Clifford, Cadastral Surveyor, in 1992
	From the W 1/16 sec. cor. of secs. 6 and 7, monumented with an iron post, 2 1/2 ins. diam., set in a collar of stone, with brass cap mkd. as described in the field notes of the 1992 resurvey.
	N. 1°17'40" W., on the N-S center line of the SW1/4 of sec. 6.
19.899	Point for the SW 1/16 sec. cor. of sec. 6, identical with Angle Point No. 6, Parcel C, sec. 6, and Angle Point No. 6, Lot 22, sec. 6, at intersection with the E-W center line of the SW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.
	SW 1/16 S 6
	1996
	This cor. will now refer to the SW 1/16 sec. cor. of sec. 6, identical with Angle Point No. 6, Lot 22, sec. 6 only.
	From this corner a rebar, 5/8 in. diam., with aluminum cap mkd. RLS 4541, bears North, 0.100 chs. dist.
20.365	The SW 1/16 sec. cor. of sec. 6, identical with Angle Point No. 6, Parcel C, sec. 6, determined in the 1992 resurvey, monumented with a stainless steel post, 2 1/2 ins. diam., set in a collar of stone, with brass cap mkd. as described in the field notes of the 1992 survey. This monument was set at intersection using the 1992 position for the center S 1/16 sec. cor. of sec. 6, which was reestablished in error.
	Monument removed.