

SURVEY OF THE THIRD STANDARD PARALLEL SOUTH,  
THROUGH A PORTION OF RANGE 64 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Beginning at the standard cor. of Tps. 12 S., Rs. 63 and 64 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the Third Standard Parallel South, through portions of Range 63 East, executed concurrently under this same group.</p> <p>East, on the S. bdy. of sec. 31, T. 12 S., R. 64 E.</p> <p>Over mountainous terrain.</p>
22.906	The 1/4 sec. cor. of sec. 6 only, hereinafter described.
37.279	<p>Point selected for the witness standard 1/4 sec. cor. of sec. 31, T. 12 S., R. 64 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">WC T12S R64E 1/4 S31 —————&gt; 2003</p>
40.000	True point for the standard 1/4 sec. cor. of sec. 31, T. 12 S., R. 64 E., falls on a steep precipice where it is impracticable to establish a permanent monument.
62.906	The closing cor. of secs. 5 and 6, hereinafter described.
80.000	Point for the standard cor. of secs. 31 and 32, T. 12 S., R. 64 E.
	<p>Set a brass rod, 18 ins. long, 1/2 in. diam., 10 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">SC T12S R64E S31   S32 ————— ————— 2003</p>
	<p>Land, mountainous. Soil, sandy gravel. Undergrowth, creosote and cacti.</p> <hr/>