

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 32 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T32S R65E R66E 1/4 S 1 S 6</p> <p style="text-align: center;">1997</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°10'30" E., beginning new measurement.</p> <p>39.756 The cor. of Tps. 31 and 32 S., Rs. 65 and 66 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the 1932 dependent resurvey of the S. bdy. of T. 31 S., R. 66 E., executed by C.S. Swanholm under Group No. 157, and a mound of stone S. of the corner.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 32 S., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of Portions of the Survey Executed by T.A. Magee in 1883, the Resurvey Executed by J.W. Hardison in 1947, and the Resurvey Executed by E.W. Sibley in 1961</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, flush with the surface of the ground, with brass cap mkd. as described in the field notes of the 1947 dependent resurvey executed by J.W. Hardison under Group No. 239.</p> <p>N. 0°31'00" W., bet. secs. 28 and 29.</p> <p>40.015 The 1/4 sec. cor. of secs. 28 and 29, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with aluminum cap mkd. KEITH CO PLS 8866, determined by Christopher L. Albers, Nevada Professional Land Surveyor No. 8866, as shown on Record of Survey File 71, Page 95, on file in the office of the Clark County Recorder. This is accepted as a careful and faithful determination of the corner.</p> <hr/> <p>N. 0°28'00" W., beginning new measurement.</p> <p>40.036 The cor. of secs. 20, 21, 28, and 29, monumented with a rebar, 5/8 in. diam., projecting 12 ins. above the E. bank of a concrete flood channel, with aluminum cap mkd. KEITH CO PLS 8866 S20 S21 S28 S29; perpetuated by Christopher L. Albers, Nevada Professional Land Surveyor No. 8866, in 1994 as shown on Record of Survey File 71, Page 95, on file in the office of the Clark County Recorder. This is accepted as a careful and faithful perpetuation of the original corner.</p> <hr/>
---------------	---