

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>20.096 The cor. of secs. 4 and 5 only, perpetuated by Kenneth L. Haskew, Nevada Professional Land Surveyor No. 3849, in 1982, monumented with a rebar, 5/8 in. diam., firmly set in concrete and in a mound of stone, with aluminum cap mkd. HASKEW ENG T10S R47E S32 S5 S4 T11S R47E RLS3849, as recorded in Nye County, Nevada, Record of Survey 61094. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p>						
	<hr/>						
	<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p>						
	<hr/>						
	<p>Reestablishment of the Survey Executed by O.E. Brashears, U.S. Deputy Surveyor, in 1906</p>						
	<hr/>						
	<p>From the cor. of secs. 26, 27, 34 and 35, monumented with a basalt stone, 18x10x8 ins., firmly set, mkd. with 1 notch on the south and 2 notches on the east edges, and a mound of stone west of the corner.</p>						
	<p>At the corner point</p>						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p>						
	<table border="1" data-bbox="860 1039 1015 1155"> <tr> <td>T11S R47E</td> <td></td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> </table>	T11S R47E		S27	S26	S34	S35
T11S R47E							
S27	S26						
S34	S35						
	<p>2004</p>						
	<p>Deposit the mkd. stone alongside the stainless steel post and rebuild the mound of stone west of the corner.</p>						
	<p>N. 0°01'30" E., bet. secs. 26 and 27.</p>						
	<p>40.321 The 1/4 sec. cor. of secs. 26 and 27, monumented with a basalt stone, 16x12x6 ins., firmly set, mkd. 1/4 on the west face and a mound of stone west of the corner.</p>						
	<p>At the corner point</p>						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p>						
	<table border="1" data-bbox="860 1648 1015 1743"> <tr> <td>T11S R47E</td> <td></td> </tr> <tr> <td>1/4</td> <td></td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> </table>	T11S R47E		1/4		S27	S26
T11S R47E							
1/4							
S27	S26						
	<p>1998</p>						
	<p>Deposit the mkd. stone alongside the stainless steel post.</p>						
	<hr/>						
	<p>N. 0°08'10" W., beginning new measurement.</p>						