

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.050	The cor. of secs. 4 and 5 only, on the N. bdy. of the Tp., hereinbefore described.
<hr/> SUBDIVISION OF SECTION 4, T. 11 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
	From the 1/4 sec. cor. of secs. 4 and 9.
	N. 0°01'20" W., on the N-S center line of sec. 4.
7.60	Powerline, NW-SE.
20.060	Point for the C-S 1/16 sec. cor. of sec. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
$\begin{array}{c} C \\ S\ 1/16 \left S\ 4 \\ C \end{array}$ 1998	
40.120	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
$\begin{array}{c} T11S\ R47E \\ C\ 1/4\ S\ 4 \\ 1998 \end{array}$	
49.70	Powerline, NW-SE.
60.208	Point for the C-N 1/16 sec. cor. of sec. 4; not monumented.
80.266	The 1/4 sec. cor. of sec. 4 only, on the N. bdy. of the Tp., hereinbefore described.
<hr/> From the 1/4 sec. cor. of secs. 3 and 4. S. 89°39'00" W., on the E-W center line of sec. 4.	
20.072	Point for the C-E 1/16 sec. cor. of sec. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
$\begin{array}{c} E\ 1/16 \\ C \text{ --- } C \\ S\ 4 \\ 1998 \end{array}$	
Raise a mound of stone north of the corner.	