

331

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 6 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor N.L. Berdan in 1882
	<p>Beginning at the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., monumented with a basalt stone, 14x6x6 ins., (Record, 18x10x8 ins.), firmly set, projecting 7 ins. above the ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R40E S34 1/4 <u> </u> S 3 T7S</p> <p>2003</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>S. 88°58'30" W., bet. secs. 3 and 34.</p> <p>Descend over W. slope.</p>
0.70	Wash, drains S. 40° E.; asc. over SE. slope.
9.80	Graveled road, 20 lks. wide, bears N. 40° W. and S. 40° E., and spur, slopes S. 40° E.; desc. over SW. slope.
40.154	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R40E S33 S34 S 4 S 3 T7S</p> <p>2003</p> </div>
	<p>S. 88°58'30" W., bet. secs. 4 and 33.</p> <p>Over rolling hills.</p>
40.154	Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original cor.