

008

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 36 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by U.S. Deputy Surveyor
H.B. Maxson in 1888, and the Resurvey Executed by
U.S. Transitman N.E. Potter in 1912

From the 1/4 sec. cor. of sec. 18 only, on the W. bdy. of
the Tp., monumented with a granite stone, 24x8x5 ins., (Record
20x6x4 ins.) firmly set, projecting 12 ins. above ground,
no marks visible, alongside of which is an iron rod, 5/8 in.
diam., firmly set, projecting 4 ins. above ground, with plastic
cap mkd. JOHN H. MILTON PLS 5271, set by John H. Milton, III,
Nevada Professional Land Surveyor No. 5271, not of record.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, over a plastic-encased magnet, with
brass cap mkd.

T36N	
R32E	R33E
	1/4
	S18

2004

Deposit the 1912 stone alongside the stainless steel post.

N. 0°36'20" E., on the W. bdy. of sec. 18.

Over alkali flat.

38.212

The cor. of secs. 12 and 13 only, T. 36 N., R. 32 E.,
monumented with the rusted remains of an iron post, 2 ins.
diam., filled with concrete, firmly set in the ground, 4 ins.
below the surface, the top 16 ins. of the iron post is broken
off and laying loosely on the ground, with brass cap mkd. as
described in the field notes of T. 36 N., R. 32 E., executed
under Group No. 14.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
23 ins. in the ground, over a plastic-encased magnet, and in a
collar of stone, with brass cap mkd.

T36N	T36N
R32E	R33E
S12	S18
S13	

2004