

038

INDEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 37 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

This Independent Resurvey Supersedes a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1874. A diligent search was made for the original corners and the corners that were found are hereinafter noted.

From the point for the cor. of Tps. 36 and 37 N., Rs. 32 and 33 E., established SOUTH from the cor. of Tps. 37 and 38 N., Rs. 32 and 33 E., and EAST from the cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., to an intersection, both hereinafter described.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

T37N
R32E R33E
S36 | S31
T36N R32E
S 1

2004

The cor. is located on a rocky spur, slopes SW.

WEST, on the S. bdy. of sec. 36.

Over mountainous land.

17.751 The 1/4 sec. cor. of sec. 1 only, T. 36 N., R. 32 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the survey of a portion of the subdivisional lines of T. 36 N., R. 32 E., executed concurrently under this same group.

35.15 Jeep trail, 10 lks. wide, bears N. 15° W. and S. 15° E.

40.000 Point for the 1/4 sec. cor. of sec. 36 only.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T37N R32E
1/4 S36
T36N R32E

2004

The cor. is located on a rocky spur, slopes SW.

40.50 Drainage, dry, 20 lks. wide, drains S. 30° W., enter rolling hills.