

081

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1872 and the Resurvey and Survey Executed by U.S. Deputy Surveyor C.S. Alverson in 1880-1881
	Beginning at the cor. of secs. 15, 16, 21 and 22, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 4 ft. base, 6 ins. high, with the remains of a cottonwood post, 6x1 1/2x3/4 ins., no visible marks laying alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T30N R19E S16 S15 S21 S22
	2004
	Deposit the local pipe and the remains of the original wood post alongside the stainless steel post.
	N. 1°07'30" W., bet. secs. 15 and 16.
	Over nearly level land, covered with sagebrush and greasewood.
10.90	Mine road, 30 lks. wide, bears E. and W.
20.232	Point for the S 1/16 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	S 1/16 S16 S15
	2004
40.464	The 1/4 sec. cor. of secs. 15 and 16, monumented with a deeply embedded mound of stone, 3 ft. base, 1 ft. high. This mound of stone correlates well with other existing corners and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.