

FURTHER SUBDIVISION OF SECTION 29,
T. 19 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>From the center E 1/16 sec. cor. of sec. 29.</p> <p>N. 0°43'50" E., on the N-S center line of the NE1/4 of sec. 29.</p> <p>Over nearly level land, along the center of Riley Street (asphalt).</p> <p>9.930 Point for the center S-NE 1/64 sec. cor. of sec. 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with asphalt, over plastic encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S29 C-S-NE 1/64</p> <p style="text-align: center;">2006</p> <p>from which</p> <p>A brass tablet, 2 ins. diam., set in a concrete cylinder, 6 ins. diam., for a reference monument, bears N. 37°19'00" E., 76.8 lks. dist., mkd. RM C-S-NE 1/64 50.70 FT TO COR S29 2006 and an arrow pointing to the corner.</p> <p>A brass tablet, 2 ins. diam., set in a concrete cylinder, 6 ins. diam., for a reference monument, bears S. 41°17'10" E., 74.5 lks. dist., mkd. RM C-S-NE 1/64 49.16 FT TO COR S29 2006 and an arrow pointing to the corner.</p> <p>A brass tablet, 2 ins. diam., set in a concrete cylinder, 6 ins. diam., for a reference monument, bears S. 41°10'30" W., 78.8 lks. dist., mkd. RM C-S-NE 1/64 52.00 FT TO COR S29 2006 and an arrow pointing to the corner.</p> <p>A brass tablet, 2 ins. diam., set in a concrete cylinder, 6 ins. diam., for a reference monument, bears N. 42°57'00" W., 88.4 lks. dist., mkd. RM C-S-NE 1/64 58.34 FT TO COR S29 2006 and an arrow pointing to the corner.</p> <p>Cor. is located at the intersection of Riley St. and Bright Angel Way.</p> <p>14.895 The center N-S-NE 1/256 sec. cor. of sec. 29, determined at a PK nail and washer mkd. PLS 4046. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with asphalt, over plastic encased magnet, with brass cap mkd.</p>
---------------	---