

## 116

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 11 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of a Portion of the Survey Executed by C.F. Putnam in 1881
	<p>Beginning at the cor. of Tps. 11 and 12 S., Rs. 62 and 63 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., 6 ins. high, mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 12 S., R. 63 E., executed concurrently under this same Group.</p> <p>N. 0°35'40" W., bet. secs. 31 and 36.</p> <p>Over nearly level land.</p> <p>39.987 The 1/4 sec. cor. of secs. 31 and 36, monumented with a granite stone, 18x10x7 ins., firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S 1/4 R62E   R63E S36   S31</p> <p>2005</p> </div> <p>Deposit the original stone alongside the stainless steel post.</p>
	<p>N. 0°16'40" E., beginning new measurement.</p>
34.80	Spur, slopes W.
35.60	Gulch, 75 lks. wide, drains N. 80° E.
40.009	<p>The cor. of secs. 25, 30, 31 and 36, perpetuated by Jerry Barnson, Nevada Professional Land Surveyor No. 4046, not recorded, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. VTN ENGR CO RLS 4046, firmly set, and in a mound of stone, 3 ft. diam., 1 ft. high, alongside of which is a cement stone, 18x8x6 ins., mkd. with 5 grooves on one face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R62E R63E S25   S30 S36   S31</p> <p>2005</p> </div>