

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 12 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by C.F Putnam, U.S. Deputy Surveyor in 1881</p> <hr/>
	<p>Beginning at the standard cor. of Tps. 12 S., Rs. 63 and 64 E., monumented with a stainless steel post, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. as described in the field notes of the dependent resurvey of a portion of the Third Standard Parallel South, executed under Group No. 814.</p> <p>N. 0°28'20" W., on the E. bdy. of sec. 36.</p> <p>Over nearly level land.</p>
40.210	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original cor. This corner will now refer to the 1/4 sec. cor. of sec. 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12S R63E R64E 1/4 S36 </p> <p>2005</p> </div>
42.00	Ascend over broken and steep terrain.
80.420	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original cor. This corner will now refer to the cor. of secs. 25 and 36 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12S R63E R64E S25 S36 </p> <p>2005</p> </div>
40.210	<hr/> <p>N. 0°28'20" W., on the E. bdy. of sec. 25.</p> <p>Over broken and steep terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original cor. This corner will now refer to the 1/4 sec. cor. of sec. 25 only.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in a drill hole in solid rock, with top mkd.</p>