

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by C.F Putnam, U.S. Deputy Surveyor in 1881</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, monumented with a cement stone, 14x10x9 ins., loosely set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. with 1 groove on one face and 5 grooves on opposite face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T12S</td></tr> <tr><td style="text-align: center;">R62E</td><td style="text-align: center;">R63E</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> </table> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <p>NORTH, bet. secs. 25 and 30.</p> <p>Over nearly level land.</p>	T12S		R62E	R63E	S25	S30	S36	S31
T12S									
R62E	R63E								
S25	S30								
S36	S31								
40.234	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with a cement stone, 13x11x6 ins., loosely set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 1/4 on one face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T12S</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">R62E</td><td style="text-align: center;">R63E</td></tr> <tr><td style="text-align: center;">S25</td><td style="text-align: center;">S30</td></tr> </table> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p>	T12S		1/4		R62E	R63E	S25	S30
T12S									
1/4									
R62E	R63E								
S25	S30								
28.00	<p>N. 0°05'20" W., beginning new measurement.</p> <p>Gulch, 150 lks. wide, drains NE.</p>								
31.40	<p>Dirt road, 15 lks. wide, bears NW. and SE.</p>								
40.155	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a cement stone, 17x10x9 ins., firmly set, mkd. with 2 grooves on N. face and 4 grooves on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>								