

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor A.J. Hatch in 1868 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor J.R. Munson in 1965 Beginning at the 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 2 1/2 ft. base, 4 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 35 N., R. 37 E., executed under Group No. 427. N. 0°45'30" W., bet. secs. 15 and 16. Over nearly level land through scattered sagebrush. 5.00 From this point, a corner of barbed wire fences extending S. and S. 63° W., bears W., 0.15 chs. dist. 5.20 Graded dirt road, 10 lks. wide, bears N. 63° E. and S. 63° W. 12.00 Corner of barbed wire fences extending N. and E. 21.076 The N 1/16 sec. cor. of secs. 15 and 16, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. J.H. Milton, PLS 5271, as recorded in Humboldt County, Nevada, Document No. 2001 3312. This is accepted as a careful and faithful determination of the position of the corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. N 1/16 S16 S15 2006 Deposit rebar inside stainless steel post. Corner is located on W. side of corner of barbwire fences extending S. and E. N. 0°45'40" W., beginning new measurement. Over nearly level land through scattered sage. 0.20 Powerline, bears N. 59° W. and S. 59° E. 7.239 Point for the witness point at intersection with the southerly right-of-way line of Union Pacific Railroad, hereinafter described.
--------	---