

184

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 20 S., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

A root hole, diam. indeterminate, bears S. $38\frac{3}{4}^{\circ}$ W., 54 1/2 lks. dist.; lying downhill is the rotted wood remains with scribe marks T20S R56E S1 BT visible. (Record, S. $49\frac{1}{2}^{\circ}$ E., 64 lks.).

A white pine, 15 ins. diam., bears N. 46° W., 63 lks. dist., with the scribe marks T19S R56E S36 BT visible on weathered surface, (Record, pinion, N. $47\frac{1}{2}^{\circ}$ E.)

At the corner point

Reset iron post, 36 ins. long, 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, and add the marks 2004 to brass cap.

from which new accessories

A chiseled X followed by the letters BO, bears S. $17^{\circ}03'$ E., 154.0 lks. dist., mkd. on the top of a limestone outcrop, 3x2x2 ft. high.

A chiseled X followed by the letters BO, bears N. $2^{\circ}55'$ W., 203.4 lks. dist., mkd. on the top of a limestone outcrop, 12x4x3 ft. high, located on top of sharp spur, slopes WNW.

This control line was fully retraced, and no evidence of the intervening corners was found.

From this same corner, a mound of stone, 3 ft. base, 12 ins. high, bears S. $71^{\circ}08'$ E., 4.430 chs. dist. This mound has been determined to be a temporary mound for the position of the cor. of secs. 19, 24, 25, and 30, built by Nelson and Swanholm in the 1929 retracement: No marked stone was recovered from this mound; and correlates well with the Nelson/Swanholm record of diligently searching at 40 and 80 chain intervals along the range line; this mound shows a poor relationship with the original corner of secs. 25, 30, 31, and 36.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 S., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
T. Binge, U.S. Deputy Surveyor in 1881

From the cor. of secs. 26, 27, 34, and 35, perpetuated by Dona J. Rogers, Nevada Professional Land Surveyor No. 11192, monumented with an aluminum pipe, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, in a mound of stone, 3 ft. base, 12 ins. high, with a limestone, 12x10x7 ins., marked with 1 groove on a face, and 2 grooves on an adjacent face, recovered from below the mound and alongside the aluminum pipe, with U.S.F.S. aluminum cap mkd. T20S R56E 26 27 34 35 2001, as recorded in Clark County, Nevada, as a Corner Record, Instrument No. 20060512-00306, from which the original bearing trees