

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 S., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which new accessories</p> <p>A pinion pine, 8 ins. diam., bears N. 26 1/2° E., 81 lks. dist., mkd. X BT.</p> <p>A chiseled X followed by the letters BO, bears N. 50°55' W., 19.6 lks. dist., mkd. on the top of a limestone ledge.</p> <p>Rebuild the mound of stone, 7 ft. base, around pipe to top.</p> <hr/> <p>N. 89°26'20" W., beginning new measurement.</p> <p>40.096 The cor. of secs. 21, 22, 27, and 28.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 27, T. 20 S., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0°07'10" E., on the N-S center line of sec. 27.</p> <p>1.55 An intermittent stream, 5 lks. wide, course S. 20° W.</p> <p>3.50 A four wheel drive road, 10 lks. wide, bears E. and W.</p> <p>17.176 From this point, a rebar, 3/8 in. diam., bears West, 0.208 chs. dist., no marks found.</p> <p>20.450 Point for the C-S 1/16 sec. cor. of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S27 C</p> <p style="text-align: center;">2004</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, 1 1/2 ft. diam., bears S. 12°33' W., 0.789 chs. dist., no marks found. This monument is not utilized in the course of this survey.</p> <p>22.154 From this point, a rebar, 5/8 in. diam., firmly set, projecting 10 ins. above the ground, bears West, 0.129 chs. dist., no marks found.</p> <p>22.180 From this point, a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, and in a collar of stone, 1 ft. diam., bears West, 0.133 chs. dist., with plastic cap, mkd. CIVELWISE PLS 10026.</p> <p>28.25 Center of graded dirt road, 25 lks. wide, bears N. 60° E. and S. 60° W.,</p> <p>40.900 Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E-W center line.</p>
--------	---