

SUBDIVISION OF SECTION 2,
T. 21 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 2 and 11, perpetuated by Russell Avery, Nevada Professional Land Surveyor No. 2002, in 1973, monumented with a rebar, 1/2 in. diam., with plastic cap mkd. RE 2002, set in a mound of stone, alongside of which is a limestone, 10x10x8 ins., mkd. 1/4 on the N. face, as shown on Record of Survey File No. 27, Page No. 3, on file in the office of the Clark County recorder and is accepted as a careful and faithful perpetuation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T21S R54E S 2 1/4 — S11 2001 </div> <p>Deposit the rebar inside and bury the mkd. stone alongside the stainless steel post.</p> <p>Raise a mound of stone N. of the corner.</p> <p>N. 0°10'00" E., on the N-S center line of sec. 2.</p> <p>40.639 Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T21S R54E C 1/4 S 2 2003 </div> <p>61.000 Point for the C-N 1/16 sec. cor. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> C N 1/16 S 2 C 2003 </div> <p>71.10 Power transmission line, bears NW-SE.</p>
--------	--