DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 15 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

	1. 13 N., N. 20 E., MOUNT DIABLO MENIDIAN, NEVADA
CHAINS	Reestablishment of Portions of the Survey Executed by U.S. Deputy Surveyors H.E. Franks and J.S. Mullen in 1904, the Survey Executed by Deputy Surveyors W. Kearney and H. Thurtell in 1908, the Survey and Resurvey Executed by U.S. Surveyor W.H. Reppert in 1913-1915 and the Survey and Resurvey Executed by R.A. Pratt in 1989 From the cor. of secs. 25 and 36 only, on the E. bdy. of
	the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, in a fence extending N. and S., with brass cap mkd. as described in the field notes of the dependent resurvey of T. 15 N., R. 27 E., executed under Group No. 670.
	N. 89°58'50" W., bet. secs. 25 and 36.
	Over flats covered with widely scattered sagebrush and native grasses.
25.30	Barbed wire fence, bears SE. and NW.
34.40	Dry wash, 10 lks. wide, drains NW.
40.003	The 1/4 sec. cor. of secs. 25 and 36, monumented with a redwood post, 4x3 ins., firmly set, projecting 12 ins. above ground, no mks. visible.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.
	T15N R26E
	$\frac{525}{1/4}$
	S36
	2005
	Deposit the unmkd. redwood post alongside the stainless steel post and set a steel boundary marker post alongside.
	S. 89°59'10" W., beginning new measurement.
	Over flats covered with widely scattered sagebrush and native grasses.
6.40	Dry wash, 10 lks. wide, drains NW.
9.30	Buried fiber optic cable, bears SE. and NW.
24.10	Trail road, 20 lks. wide, bears SE. and NW.
24.80	Dry wash, 20 lks. wide, drains NE.