

254

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 23 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.75	Center of graded dirt road to Hidden Valley, 18 lks. wide, bears N. 45° W. and S. 55° E.
14.985	Point for the N-S-S 1/256 sec. cor. of secs. 32 and 33, identical with Angle Point No. 3, sec. 33, of this survey.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	N-S-S 1/256 S32 S33
	2005
29.970	Point for the N-S 1/64 sec. cor. of secs. 32 and 33, identical with Angle Point No. 5, sec. 33, of this survey.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	N-S 1/64 S32 S33
	2005
39.960	The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 23 S., R. 61 E., executed under Group No. 364, and a mound of stone, 3 ft. base, 16 ins. high, W. of the cor.
	from which
	A chiseled X followed by the letters BO, bears S. 11°41' E., 45.6 lks. dist., mkd. on the top of an igneous boulder, 2x1x1/2 ft. high.
	Add the marks T23S R61E 2005 to brass cap.
<hr/> SUBDIVISION OF SECTION 25, T. 23 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
	From the 1/4 sec. cor. of secs. 25 and 36.
	N. 0°24'40" W., on the N-S center line of sec. 25.
40.190	Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.