

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1882</p> <hr/> <p>Beginning at the cor. of secs. 19, 20, 29 and 30, determined by the Department of the Army - Corps of Engineers, from a mound of earth and pits (mound of earth and pits no longer exists, and no marked stone found) as shown on Drawing No. 15-03-01, sheet 2 of 3 sheets, date: OCT. 1948, as recorded in Clark County, Nevada, File 1, Page 10 of Surveys. This position has been perpetuated and recorded by several professional land surveyors, and is now monumented with an unrecorded brass tablet, 2 ins. diam., firmly set in concrete flush with the asphalt, mkd. "T19S R62E 19 20 29 30 PLS 10160 2006", and is accepted as the best available evidence of the position of the original corner from which accessories established by Bartlett C. Dalton, Nevada Professional Land Surveyor No. 10160</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of a concrete base for a power pole, mkd. "REFERENCE MONUMENT 102.01 CNLV PLS 10160", bears S. 44°53' W., 154.6 lks. dist.</p> <p>An aluminum tablet, 2 ins. diam., firmly set in the top of a concrete cylinder 10 ins. diam., mkd. "REFERENCE MONUMENT 68.03 CNLV PLS 10160", bears N. 43°00' W., 103.1 lks. dist.</p> <p>Cor. is located at the intersection of Centennial Parkway and Lamb Boulevard.</p> <p>S. 89°25'00" W., bet. secs. 19 and 30.</p> <p>Over nearly level land, along the northern edge of Centennial Parkway (asphalt).</p>
<p>10.545</p>	<p>The E-E 1/64 sec. cor. of secs. 19 and 30, determined by Larry E. Crow, Nevada Professional Land Surveyor No. 9399 in 1992, monumented with a brass tablet, 2 ins. diam., firmly set in concrete cylinder, 10 ins. diam., 12 ins. below surface of the ground, mkd. "NORTH LAS VEGAS T19S R62E E-E 1/64 S19 S30 PLS 9399 SURVEY MONUMENT", as recorded in Clark County, Nevada, File 62, Page 2 of Surveys and Corner Record Book 920117, Inst. 00533, sheet 3 of 18 sheets. This is accepted as a careful and faithful determination of the position of the corner from which accessories established by Larry E. Crow</p> <p>An aluminum cap, 2 ins. diam., firmly set in concrete cylinder, 10 ins. diam., 4 ins. below surface of the ground, mkd. "NORTH LAS VEGAS T R6 E RM 62.13 PLS 9399 SURVEY MONUMENT", bears N. 51° 11' E., 94.1 lks. dist.</p> <p>An aluminum cap, 2 ins. diam., firmly set in concrete cylinder, 10 ins. diam., flush with the ground, mkd. "NORTH LAS VEGAS T S R6 E RM 68.29 PLS 9399 SURVEY MONUMENT", bears S. 32°07' E., 103.5 lks. dist.</p>