

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 14 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor B. Ives in 1865, a Portion of the Dependent Resurvey Executed by Cadastral Surveyor D.A. Cannon in 1963 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.E. Williams in 1985</p> <hr/>
	<p>Beginning at the E 1/16 sec. cor. of secs. 18 and 19, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 20 E., executed under Group No. 624.</p>
	<p>S. 89°55'00" W., bet. secs. 18 and 19.</p>
	<p>Over flat ground covered with grass and sagebrush.</p>
18.54	<p>Wire fence, bears NE. and SW.</p>
19.78	<p>U.S. Highway No. 395, N. bound lane, asphalt surfaced, 36 ft. wide, bears N. and S.</p>
20.060	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the corner reestablished in the 1985 resurvey.</p>
	<p>Set a steel spike flush with the surface of the asphalt, mkd. with an "X" on top.</p>
	<p>from which</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over plastic-encased magnet, for a new reference monument, bears N. 52°50' E., 121.2 lks. dist., with brass cap mkd. RM 1/4 S18 80.0 FT TO COR 2005 and an arrow pointing to cor.</p>
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over plastic-encased magnet, with a steel fence post alongside, for a new reference monument, bears S. 39°59' E., 121.2 lks. dist., with brass cap mkd. RM 1/4 S19 80.0 FT TO COR 2005 and an arrow pointing to cor.</p>
	<p>Cor. is located on the W. side of the N. bound lane of U.S. Highway No. 395, asphalt surfaced, 36 ft. wide, bears N. and S.</p>
20.83	<p>U.S. Highway No. 395, S. bound lane, asphalt surfaced, 36 ft. wide, bears N. and S.</p>
24.44	<p>Power line, bears SE. and NW.</p>
26.80	<p>Improved gravel road, bears NE. and SW.</p>
40.120	<p>The W 1/16 sec. cor. of secs. 18 and 19, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 14 N., R. 20 E., executed under Group No. 624.</p> <hr/>