DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,

T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA CHAINS Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1868 From the cor. of secs. 3, 4, 33 and 34, monumented with a basalt stone, 14x10x9 ins., firmly set 8 ins. in the ground, mkd. with 3 grooves on the east and west faces. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R31E S33 S34 S 4 S 3 T19N 2005 Deposit the mkd. stone alongside the stainless steel post. From this cor., a galvanized iron pipe of unknown origin, 4 ins. diam., projecting 15 ins. above the ground, bears WEST, 0.015 chs. dist. N. 89°47'50" W., bet. secs. 4 and 33. Over nearly level land, covered with greasewood, rabbit brush, sagebrush and native grass. 26.60 West canal, 40 lks. wide, course SW. 40.148 The 1/4 sec. cor. of secs. 4 and 33, monumented with a basalt stone, 12x8x7 ins., firmly set 8 ins. in the ground, mkd. 1/4 on N. face. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T20N R31E S33 T19N 2005

Deposit the mkd. stone alongside the stainless steel post.

From this cor., a galvanized iron pipe of unknown origin, 4 ins. diam., projecting 15 ins. above the ground, bears WEST, 0.015 chs. dist.