	T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	
80.344	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R31E
	S31 S32
	S 6 S 5
	T1'9N
	2006
	N. 89°45'30" W., bet. secs. 6 and 31.
	Over nearly level land, along road.
40.172	The 1/4 sec. cor. of secs. 6 and 31, monumented with a rebar of unknown origin, 5/8 in. diam., 18 ins. long, firmly set 16 ins. in the ground. This rebar has been utilized and accepted by various professional land surveyors and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R31E
	S31
	$\frac{1/4}{S} {6}$
	T19N
	2006
	Deposit rebar alongside stainless steel post.
	Corner is located 3.0 lks. N. of fences extending S. and E.
	DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Surveys Executed by U.S. Deputy Surveyor E.B. Monroe in 1868 and 1874
	From the cor. of secs. 25 and 36, monumented with a concrete post, 3 ins. diam., 20 ins. long, firmly set flush with the surface of the ground, with brass tablet, 2 1/2 ins. diam., mkd. as described in the field notes of the dependent resurvey of a portion of the W. bdy. of T. 20 N., R. 32 E., executed under Group No. 719.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,