

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA	
CHAINS	Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1868.
	From the cor. of secs. 25, 30, 31 and 36, monumented with a basalt stone, 14x12x5 ins., firmly set 6 ins. in the ground, mkd. with 1 groove on S. face and 5 grooves on N. face.
	At the corner point
į	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E R31E <u>S25 S30</u> S36 S31
	2005
	Deposit the mkd. stone alongside the stainless steel post.
	N. 0°04'00" W., bet. secs. 25 and 30.
	Over nearly level ground, covered with greasewood and rabbit brush, sagebrush and native grass.
40.137	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E R31E 1/4 S25 S30
	2005
41.50	Trail road, bears E. and W.
80.274	The cor. of secs. 19, 24, 25 and 30, monumented with a basalt stone, 18x12x10 ins., firmly set 8 ins. in the ground, mkd. with 2 grooves on S. face and 4 grooves on N. face, with a rebar, 5/8 in. diam., 18 ins. long and a plastic cap, 1 in. diam., unreadable, set alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R30E R31E S24 S19 S25 S30
	2005