

## 333

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
60.181	From this point, a rebar of unknown origin, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, bears SOUTH, 0.013 chs. dist. This rebar was not utilized during the course of this survey.
60.705	Point for a witness point and intersection with the apparent centerline of the existing improved gravel road, hereinafter described.
77.320	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 33, T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.
	N. 0°14'20" W., on the N-S center line of sec. 33.
19.872	Point for the C-S 1/16 sec. cor. of sec. 33.
	POINT NOT MONUMENTED.
39.744	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T20N R31E C 1/4 S33  2006
52.946	Apparent centerline of an existing improved gravel road, bears NE. and SW.
53.668	Intersection with a line 30 ft. westerly and perpendicular to the apparent centerline of the existing improved gravel road.
59.442	The C-N 1/16 sec. cor. of sec. 33, determined by Steven E. Hampton, Nevada Professional Land Surveyor No. 10142, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set 14 ins. in the ground, with aluminum cap, 2 ins. diam., mkd. PLS 10142 1/16, with the remains of an iron pipe, 2 ins. diam., 15 ins. long, alongside rebar, as recorded in Churchill County, Nevada, File No. 340350 Record of Survey. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.